BALTIMORE METROPOLITAN PLANNING ORGANIZATION BALTIMORE REGIONAL TRANSPORTATION BOARD

RESOLUTION #23-17 ADOPTING SYSTEM PERFORMANCE TARGETS RELATED TO LEVEL OF TRAVEL TIME RELIABILITY AND TRUCK TRAVEL TIME RELIABILITY

WHEREAS, the Baltimore Regional Transportation Board (BRTB) is the designated metropolitan planning organization (MPO) for the Baltimore region, encompassing the Baltimore Urbanized Area, and includes official representatives of the cities of Annapolis and Baltimore, the counties of Anne Arundel, Baltimore, Carroll, Harford, Howard, and Queen Anne's, as well as representatives of the Maryland Department of Transportation, the Maryland Department of the Environment, the Maryland Department of Planning, the Maryland Transit Administration, and Annapolis Transit; and

WHEREAS, the BRTB, as the MPO for the Baltimore region, has the responsibility under the provisions of the Infrastructure Investment and Jobs Act (IIJA), preceded by the Fixing America's Surface Transportation Act, for developing and carrying out a continuing, cooperative and comprehensive transportation planning process for the metropolitan area; and

WHEREAS, the IIJA continued the implementation of performance-based planning and programming to achieve desired performance outcomes for the multimodal transportation system, including setting targets for future performance by states, providers of public transportation, and MPOs; and

WHEREAS, the Federal Highway Administration (FHWA) issued a final rule establishing performance measures for state departments of transportation (DOTs) and MPOs to use to assess the performance of the National Highway System (NHS) under the National Highway Performance Program (NHPP). These include two measures related to Level of Travel Time Reliability (LOTTR) – (1) percent of person-miles traveled on the Interstate System that are reliable and (2) percent of person-miles traveled on the Non-Interstate NHS that are reliable, as well as a Truck Travel Time Reliability (TTTR) Index or ratio of Interstate System mileage indicating reliable truck travel times; and

WHEREAS, the Maryland Department of Transportation (MDOT) has coordinated with the Baltimore Regional Transportation Board and Baltimore Metropolitan Council staff on a method for developing 2-year and 4-year targets for the Baltimore region (see Attachment 1); and

WHEREAS, MDOT developed information and targets toward compliance with the law and regulations by the October 1, 2022 due date established for these performance targets and communicated the relevant information and targets to the FHWA. MPOs must either support the State target or establish their own quantifiable 4-year targets within 180 days of the State target establishment [i.e., in the case of the BRTB, by March 31, 2023].

NOW, THEREFORE BE IT RESOLVED that the Baltimore Regional Transportation Board as the Metropolitan Planning Organization for the Baltimore region adopts these system performance targets related to travel time reliability for the Baltimore region, as described in Attachment 1.

I HEREBY CERTIFY that the Baltimore Regional Transportation Board as the Metropolitan Planning Organization for the Baltimore region approved the aforementioned resolution at its March 28, 2023 meeting.

3-28-23

Date

Sam Snead, Chair Baltimore Regional Transportation Board

	Baseline	2-Year	4-Year	2-Year	4-Year
Performance Measure	2017	Targets*	Targets*	Targets	Targets
		(2019)	(2021)	(2023)***	(2025)***
LUTTR (Interstate) measure:					
Percent of person-miles traveled	71.5%	72.1%	72.1%	72.9%	72.9%
on the Interstate System that are					
reliable					
<mark>Observed – region</mark>	<mark>74.1%</mark>	<mark>71.6%</mark>	<mark>88.4%</mark>		
LOTTR (non-Interstate) measure:					
Percent of person-miles traveled	82.0%	NA	81.7%	79.4%	79.4%
on the non-Interstate NHS that					
are reliable					
Observed - region	<mark>79.8%</mark>	<mark>78.9%</mark>	<mark>91.3%</mark>		
TTTR Index: Ratio of Interstate					
System mileage indicating	1.87	1.87	1.88	2.06	2.06
reliable truck travel times					
Observed- region	<mark>2.08</mark>	<mark>2.03</mark>	<mark>1.64</mark>		

System Performance Targets Related to Travel Time Reliability for the Baltimore Region

* set in 2018 using 2017 as baseline year – region adopted statewide targets

** - regional targets are average of 2017 and 2019 observed values

About Level of Travel Time Reliability (LOTTR) Targets:

WHO: State DOTs, as well as MPOs with Interstate and/or non-Interstate NHS within their metropolitan planning area.

WHY: Through MAP-21, Congress required FHWA to establish measures to assess performance in 12 areas, including performance on the Interstate and non-Interstate NHS.

HOW: Level of Travel Time Reliability (LOTTR) is defined as the ratio of the longer travel times (80th percentile) to a "normal" travel time (50th percentile), using data from FHWA's National Performance Management Research Data Set (NPMRDS) or equivalent. Data are collected in 15-minute segments during all time periods between 6 a.m. and 8 p.m. local time. The measures are the percent of person-miles traveled on the relevant portion of the NHS that are reliable. Person-miles take into account the users of the NHS. Data to reflect the users can include bus, auto, and truck occupancy levels.

About Truck Travel Time Reliability (TTTR) Targets:

The TTTR index is a ratio comparing the time it takes trucks to travel segments of the NHS in congested conditions (as shown by the 95th percentile time) relative to the time it

takes to make a trip in "normal" conditions (as shown by the 50th percentile time). For example, say a truck takes 56 minutes to travel a segment of the NHS that normally takes 30 minutes. This translates into a ratio of 56 minutes / 30 minutes, or 1.87. This is what a TTTR index of 1.87 means.

Federal regulations require the use of the 95th percentile time as the indicator of congested conditions for truck travel (as opposed to the 80th percentile time used in the LOTTR measures). Here is the FHWA's rationale for using the 95th percentile time for truck travel (from the final rule on travel time reliability):

"FHWA believes that the 95th percentile travel time needs to be considered in the freight measure to account for the events that could impact on-time delivery as shippers, carriers, and receivers desire on-time/just-in-time delivery of goods and plan their trips by building in enough time to meet delivery requirements. For these reasons, FHWA elected to maintain the 95th percentile in the truck reliability calculation."

HOW: Freight movement will be assessed by the TTTR Index. Reporting is divided into five periods: morning peak (6-10 a.m.), midday (10 a.m. - 4 p.m.) and afternoon peak (4-8 p.m.) Mondays through Fridays; weekends (6 a.m. - 8 p.m.); and overnights for all days (8 p.m. - 6 a.m.). The TTTR ratio will be generated by dividing the 95th percentile time by the normal time (50th percentile) for each segment. The TTTR Index will be generated by multiplying each segment's largest ratio of the five periods by its length, then dividing the sum of all length-weighted segments by the total length of Interstate.

State DOTs and MPOs will have the data they need in FHWA's National Performance Management Research Data Set (NPMRDS) as the data set includes truck travel times for the full Interstate System. State DOTs and MPOs may use an equivalent data set if they prefer.

Source: FHWA Fact Sheet